

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 382 022 A3

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 90101589.1

(51) Int. Cl.⁵: A61F 13/15

(22) Date of filing: 26.01.90

(30) Priority: 08.02.89 JP 29390/89

(43) Date of publication of application:
16.08.90 Bulletin 90/33

(54) Designated Contracting States:
DE ES FR GB

(98) Date of deferred publication of the search report:
07.08.91 Bulletin 91/32

(71) Applicant: Kao Corporation
14-10, Nihonbashi Kayabacho 1-chome
Chuo-Ku Tokyo 103(JP)


(72) Inventor: Shimizu, Shigeyuki
793-81, Hiramatsuhoncho
Utsunomiya-shi-Tochigi(JP)
Inventor: Toyoda, Harumitsu
117, Koedomachi
Utsunomiya-shi, Tochigi(JP)
Inventor: Senoo, Masamichi
4594, Ichihana, Ichikaimachi
Haga-gun, Tochigi(JP)
Inventor: Abe, Keiji
2789, Ishicho
Utsunomiya-shi, Tochigi(JP)

(74) Representative: Dickel, Klaus, Dipl.-Ing.
Jullius-Kreis-Strasse 33
W-8000 München 60(DE)

(54) Absorbent article.

(57) An absorbent article such as disposable diaper, effective to prevent liquid from leaking, comprises a liquid-impermeable back sheet (13), a liquid-permeable top sheet (12), an absorbent (14) provided between the back sheet and the top sheet and a liquid-permeable surface sheet (15) fixed on the top sheet at both ends of the surface sheet at the longitudinal direction of the article, however not fixed thereon at the intermediate part.

Fig.2



EP 0 382 022 A3



European
Patent Office

EUROPEAN SEARCH REPORT

Application Number

EP 90 10 1589

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
Y	US-A-4 662 877 (F.C. WILLIAMS) * Abstract; column 3, lines 26-39; figures 2,4 *	1-5	A 61 F 13/15
Y	FR-A-6 611 13 (D. GOLDBERG) * Page 1, lines 29-58; figures 1-2 *	1-5	
A	GB-A-2 161 059 (KIMBERLY-CLARK) * Page 1, line 117 - page 2, line 11; figure 4 *	3-5	
E	EP-A-0 359 410 (PROCTER & GAMBLE) * Column 3, lines 29-30,51-53; column 4, lines 28-53; column 6, line 53 - column 7, line 3; column 7, lines 12-21,26-29; figures 1-2 *	1-5	
P,X	US-A-4 808 176 (KIMBERLY-CLARK) * Column 4, line 31 - column 5, line 19; column 6, lines 41-43; column 7, lines 17-30; figure 2 *	1	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			A 61 F
Place of search		Date of completion of search	Examiner
The Hague		03 May 91	NICE P.R.
CATEGORY OF CITED DOCUMENTS			
X: particularly relevant if taken alone		E: earlier patent document, but published on, or after the filing date	
Y: particularly relevant if combined with another document of the same category		D: document cited in the application	
A: technological background		L: document cited for other reasons	
O: non-written disclosure			
P: intermediate document		&: member of the same patent family, corresponding document	
T: theory or principle underlying the invention			

⑫

EUROPEAN PATENT APPLICATION

⑲ Application number: 90101589.1

⑤① Int. Cl.⁵: **A61F 13/15**

⑳ Date of filing: 26.01.90

③⑦ Priority: 08.02.89 JP 29390/89

④③ Date of publication of application:
16.08.90 Bulletin 90/33

⑥④ Designated Contracting States:
DE ES FR GB

⑦① Applicant: Kao Corporation
14-10, Nihonbashi Kayabacho 1-chome
Chuo-Ku Tokyo 103(JP)

⑦② Inventor: Shimizu, Shigeyuki
793-81, Hiramatsuhoncho
Utsunomiya-shi-Tochigi(JP)
Inventor: Toyoda, Harumitsu
117, Koedomachi
Utsunomiya-shi, Tochigi(JP)
Inventor: Senoo, Masamichi
4594, Ichihana, Ichikalmachi
Haga-gun, Tochigi(JP)
Inventor: Abe, Keiji
2789, Ishicho
Utsunomiya-shi, Tochigi(JP)

⑦④ Representative: Dickel, Klaus, Dipl.-Ing.
Julius-Kreis-Strasse 33
D-8000 München 60(DE)

⑤④ Absorbent article.

⑤⑦ An absorbent article such as disposable diaper, effective to prevent liquid from leaking, comprises a liquid-impermeable back sheet, a liquid-permeable top sheet, an absorbent provided between the back sheet and the top sheet and a liquid-permeable surface sheet fixed on the top sheet at both ends of the surface sheet at the longitudinal direction of the article, however not fixed thereon at the intermediate part.

EP 0 382 022 A2

Abstract Article

The present invention relates to an absorbing article such as disposable diaper, and more particularly, to an absorbing article provided with an upper sheet for leakage prevention and improved absorbing performance.

5

Prior art

The major function of an absorbing article such as disposable diaper is to absorb the wearer's excreta without permitting them to soil any articles (such as clothing) in contact with the wearer.

10 A prior disposable diaper is provided with an elastic member at its sideflaps extending from the side ends of the absorber to prevent the liquid from leaking out because the side flaps may come into close contact with the wearer's crotch by the elastic function of the elastic member. Japanese Utility Model Publication A No. 58-18520 and Japanese Patent publication A No. 58-53702 show that the side flaps have a pocket or an antileakage wall.

15 The conventional absorbing article such as disposable diaper is usually constructed such that the liquid-permeable sheet placed on the absorber is fixed to the absorber. A disposable diaper as disclosed in Japanese Patent Publication No. 26175/1978 has a laminated structure so that the liquid-permeable top sheet is peeled off to dispose of wastes easily. A disadvantage of this disposable diaper is that being fixed over its entire surface, the top sheet in contact with the wearer's skin does not follow the wearer's movement but is liable to get out of the wearer's skin. A disposable diaper as disclosed in Japanese Patent Publication No. 29932/1979 has an inner sheet which is constructed such that the central part can be separated and disposed of together with wastes. This disposable diaper also has the same disadvantage as mentioned above because the inner sheet is fixed along the entire periphery of the liquid-absorbing pad.

20 There has been no absorbing article which is constructed such that the liquid-permeable sheet placed on the absorber is fixed at its both ends to the absorber, or the surface sheet, or the liquid-impermeable back sheet, with its intermediate part unfixed over its entire width.

The conventional absorbing article such as disposable diaper is provided with elastic side flaps to prevent the leakage of excreta such as urine and feces. The side flaps are connected to the absorber. The absorbing article also has an absorber which is deformed comparatively easily, and the deformed absorber 25 is liable to separate from the wearer's crotch. When the absorber separates from the wearer's crotch, the flaps arranged on the sides of the absorber follow the movement of the absorber and hence separate from the wearer's crotch, with the result that the flaps lose their function to prevent leakage. When the absorber is separate from the wearer's crotch, it will not be able to absorb even a small quantity of excreta.

35

Summary of the invention

It is an object of the present invention to provide an absorbing article which is free of the above-mentioned disadvantage that the absorber separates from the wearer's crotch, permitting the wearer's excreta to leak. The absorbing article of the present invention is constructed such that even when the absorber separates from the wearer's crotch, it does not permit the wearer's excreta to leak.

To achieve this object, the present inventors carried out a series of researches which led to the finding that a liquid-permeable sheet remains in close contact with the wearer's crotch if it is placed on the top sheet above the absorber, with its both ends in the lengthwise direction fixed and its intermediate part unfixed. The present invention was completed on the basis of this finding.

45 The gist of the present invention resides in an absorbing article of the type having a liquid-impermeable back sheet, a liquid-permeable top sheet, an absorber placed between said two sheets, and a liquid-permeable upper sheet placed on said top sheet, characterized in that said upper sheet is placed with its both ends in the lengthwise direction fixed and its intermediate part unfixed.

50 The invention provides an absorbent article which comprises a liquid-impermeable back sheet, a liquid-permeable top sheet, an absorbent provided between the back sheet and the top sheet and a liquid-permeable surface sheet fixed on the top sheet at both ends of the surface sheet at the longitudinal direction of the article, however not fixed thereon at the intermediate part.

It is preferable that the surface sheet is shorter than the top sheet at the longitudinal direction of the article when it is not used.

It is also preferable that the surface sheet has the central part which may fall downwardly of the peripheral part when it has a weight of 40 grams on the central part.

It is preferred that at least the peripheral part of the surface sheet comprises an elastic material. The surface sheet may be composed totally of an elastic material. Alternatively it may have an elastic member such as an elastic strip, in particular on the side ends thereof.

It is preferable that the peripheral part of the surface sheet is provided to be upper than the peripheral part of the article when it is not used.

The surface sheet may be made of a liquid-impermeable material such as nonwoven fabric, film and net.

The absorber may consist of flap pulp which preferably contain a superabsorbent polymer such as starch, cellulose, synthetic polymers, a graft-copolymer of starch and acrylic acid or a salt thereof, a saponified product of a graft copolymer of starch and acrylonitrile, a crosslinked product of sodium carboxymethylcellulose and a polymer of acrylic acid or a salt thereof, which can afford absorption of liquid 20 times or more as much as its weight, getting gel.

The top sheet may be composed of nonwoven fabrics, film or net, being liquid-permeable. It preferably is water-repellent at its peripheral part and permeable at the central part.

The back sheet is preferably composed of a low density polyethylene sheet having a thickness of 10 to 60 microns, more preferably being porous to allow much humidity to go out.

The elastic member may be composed of polyurethane, natural rubber or fibers which are shrinkable when they are wet with water.

The absorbing article of the present invention is constructed such that the liquid-permeable upper sheet is placed on the top sheet above the absorber, with its both ends in the lengthwise direction fixed to the absorber, or the liquid-permeable top sheet, or the liquid-impermeable back sheet, and its intermediate part unfixed over its entire width. Therefore, the intermediate part of the liquid-permeable upper sheet easily comes into close contact with the wearer's crotch without being affected by the deformation of the absorber.

The absorbing article of the present invention denotes a disposable diaper or the like to absorb excreta. In this invention, the absorbing article is not limited to the diaper which is worn by babies and incontinent patients; but it may also be applied to briefs for incontinent patients.

The absorbing article of the present invention effectively absorbs the wearer's excreta (urine and feces) and prevents their leakage, because it is constructed such that the intermediate part of the liquid-permeable upper sheet is not fixed to the absorber and hence it comes into close contact with the wearer without being affected by the deformation of the absorber.

The absorbing article of the present invention absorbs the wearer's excreta in the following manner. Excreta are received by the intermediate part of the liquid-permeable upper sheet and then absorbed by the absorber. The intermediate part of the liquid-permeable upper sheet comes into close contact with the wearer's crotch when the diaper is worn, so that it receives the wearer's excreta almost completely without leakage and introduces them to the center of the absorber, permitting the absorber to fully exhibit its absorbing performance.

The free intermediate part of the liquid-permeable upper sheet works in concert with the absorber in the following manner. Since the absorber is under the intermediate part of the liquid-permeable upper sheet, it absorbs the excreta received by the intermediate part of the liquid-permeable upper sheet. In some embodiments, the intermediate part of the liquid-permeable upper sheet comes into contact with the top sheet, so that the excreta received by the intermediate part are rapidly introduced to the absorber via contact points.

The important effect of the present invention is the ability of the diaper to receive the wearer's excreta almost completely without leakage and to introduce them to the center of the absorber, thereby making full use of the absorbing performance, which is attributed to the fact that the liquid-permeable upper sheet has the intermediate part which almost independently comes into close contact with the wearer's crotch. In addition, the diaper of the present invention can hold solid excreta such as feces without leakage. Another effect of the present invention is the ability of the liquid-permeable upper sheet to be easily removed from the diaper proper so that it can be discarded together with excreta, which is attributed to the fact that the liquid-permeable upper sheet is fixed at their ends with a limited amount of fixing force.

Brief Description of the Drawings:

The accompanying drawings show an embodiment of the absorbing article of the present invention. Fig. 1 is an expanded plan view of the diaper, with a part cut away. Fig. 2 is a sectional view of the diaper in

worn state, taken along the line A-A of Fig. 1.

- 11 ... Diaper
- 12 ... Top sheet
- 13 ... Back sheet
- 5 14 ... Absorber
- 15 ... Upper sheet
- 16 ... Tape fastener
- 17 ... Elastic body
- 21 ... Back waist part
- 10 22 ... Crotch part
- 23 ... Front waist part
- 24 ... Side flap
- 25 ... End
- 26 ... End
- 15 27 ... Free part
- 28 ... Fixing means
- 29 ... Fixing means

In the natural configuration which the diaper of the invention has before the use, L_1 is a length at the longitudinal direction of the surface sheet and L_2 is a length at the longitudinal direction of the top sheet. It is preferable that $0.3L_2 \leq L_1 \leq 0.98L_2$, more preferably $0.5L_2 \leq L_1 \leq 0.90L_2$. When L_1 is smaller than 0.3 of L_2 , the diaper will become much less fit for a wearer. When L_1 is larger than 0.98 of L_2 , the space between the surface sheet and the top sheet will be too smaller to provide the advantage effectively.

25 Example: 1

The preferred embodiment of the present invention will be described in more detail with reference to the accompanying drawings. Although the following description of the preferred embodiment is based on a disposable diaper, the scope of the present invention is not restricted to it.

30 The disposable diaper pertaining to the present invention is shown in Fig. 1 which is an expanded plan view, with a part cut away for the illustration of the structure, and with the side that comes into contact with the wearer upward.

As shown in Fig. 1, the disposable diaper 11 is made up of a liquid-impermeable back sheet 13, a liquid-permeable top sheet 12, an absorber 14, and a liquid-permeable upper sheet 15. It consists of the back waist part 21, the front waist part 23, and the crotch part 22, and it has the side flaps 24. In addition, it may optionally have a pair of tape fasteners 16 and a pair of elastic bodies 17 within the side flaps, which will improve the function and performance of the diaper.

According to this structure of the diaper 11, the liquid-impermeable back sheet 13 is placed between the liquid-impermeable back sheet 13 and the liquid-permeable top sheet 12, and the liquid-permeable upper sheet 15 is placed on the liquid-permeable top sheet 12. According to a more desirable embodiment, the optional elastic bodies 17 are placed between the back sheet 13 of the side flap 24 and the top sheet 12 of the side flap 24, and the paired tape fasteners 16 are fixed to the back waist part 21 of the side flap 24.

45 The diaper 11 is elongated in its lengthwise direction. The back sheet 13 and the top sheet 12 have almost the same length and width. The backsheet 13 is usually made of low-density opaque polyethylene sheet having a thickness of 10 μm to 60 μm . It should preferably be a porous sheet which is permeable to water vapor but is impermeable to liquids. Moreover, the porous sheet should preferably be one which makes as small rustling noise as possible when crumpled. The top sheet 12 is usually made of a nonwoven fabric having a basis weight of 15-40 g/m². It should preferably have a water-repellent periphery and a hydrophilic central part.

The elastic body 17 is usually made of polyurethane rubber or natural rubber in the form of string or ribbon. Each elastic body 17 consists of 1 to about 5 rubber strings or ribbons. The length of the elastic body 17 is about 30% to 60% of the length of the diaper. The elastic body 17 should be stretchable about 1.3 to about 2.0 times its free length.

55 The absorber 14 is usually a pad of crushed softwood kraft pulp covered by water-absorbing paper. It should preferably contain a polymeric absorber. The pad usually weighs about 10 g to 40 g.

The liquid-permeable upper sheet 15 is placed on the top sheet 12. It is fixed to the above-mentioned top sheet 12 at both ends 25 and 26 of the diaper in its lengthwise direction, with its intermediate free part

27 unfixed. The width of the upper sheet 15 should preferably be about 30% to about 70% of the width of the diaper 11. Especially, it should be narrower than the minimum width of the crotch section 22 of the absorber 14. This makes better use of the absorber 14. The length of the upper sheet 15 may not equal that of the diaper 11 but should preferably be shorter substantially. The flat shape of the upper sheet 15 should preferably be such that the width of the free part 27 is narrow and the width of the ends 25 and 26 is wide so that the upper sheet 15 comes into close contact with the wear's crotch. However, there could be an instance where the free part 26 is as wide as or wider than the ends 25 and 26. The upper sheet 15 may be made of a nonwoven fabric, reticulated sheet, porous sheet, or elastic sheet which is permeable to liquids.

When worn, the diaper has a shape as shown in Fig. 2 which is a sectional view taken along the line A-A of Fig. 1. The liquid-permeable upper sheet 15 is fixed to the liquid-permeable top sheet 12 by the fixing means 28 and 29 at the ends 25 and 26, but the free part 27 is not fixed. The length of the free part 27 should preferably be substantially shorter than the distance between the inner ends of the fixing means 28 and 29 when the diaper is stretched flat. With these dimensions, the free part 27 separates from the absorber 14, as shown in Fig. 2. The fixing means 28 and 29 should be at two positions in the lengthwise direction of the diaper 11 and they should also be at the position where the free part 27 exists. The preferred position is within the range of about 10 mm to about 50 mm from the front and rear ends in the lengthwise direction of the diaper 11. The width of the fixing means 28 and 29 should preferably be close to the front width of the upper sheet 15. The area of the fixing means 28 and 29 is not specifically limited. The peel strength of the top sheet 12 and upper sheet 15 at the fixing means 28 and 29 should be such that the upper sheet 15 does not peel off while the diaper is worn but can be peeled off without any loss of strength when it is to be peeled off for the disposition of excreta. The specific fixing means 28 and 29 include hot-melt bonding, heat bonding, ultrasonic bonding, sewing, and hook-loop combination.

In the embodiment shown in Figs. 1 and 2, the liquid-permeable upper sheet 15 is placed on the liquid-permeable top sheet 12 and the top sheet 12 is arranged all over the diaper 11. However, it is not necessary that the top sheet 12 should exist under the entire area of the upper sheet 15. In this case, the fixing means 28 and 29 of the upper sheet 15 are partly tied up with the back sheet.

Comparative Example 1.

A disposable diaper used here consists of a liquid-permeable top sheet, a liquid-impermeable back sheet, and an absorber.

Example 2

A diaper used here is the same diaper as used in Comparative Example 1 except further comprising a surface sheet composed of hydrophilic nonwoven fabric produced by melting polyolefine fiber.

Example 3

The same diaper as used in Comparative Example 1 further comprises a surface sheet of nonwoven fabric of rayon produced by water-needling.

Example 4

The same diaper as used in Comparative Example 1 further comprises a surface sheet composed of a polyolefine net.

Comparative Example 2

The same diaper as used in Comparative Example 1 further comprises a surface sheet of hard dury polyvinyl chlorid having perforates of 5 mm diameter at intervals of 10 mm.

Example 5

The same diaper as used in Comparative Example 1 further comprises a surface sheet of heat-fused polyolefin fiber, being shorter at the longitudinal direction than the top sheet.

Example 6

The same diaper as used in Comparative Example 1 further comprises a surface sheet of heat-fused polyolefin fiber, being shorter at the longitudinal direction than the top sheet, being provided with an elastic member of natural rubber at the peripheral part.

The above obtained diapers were tested with a model imitating a baby weighing 10 kg in view of the antileakage property. Ten grams of a test liquid at a time was repeatedly injected therein until the liquid had been found to leak. Results are shown in terms of the amount of the absorbed liquid until the leaking at the back when the model was placed in supine position and then the front, in ortostatic position.

injection rate	Amount of leakage	Comp. Ex. 1	Ex. 2	Ex. 3	Ex. 4
3g/second	the back	30	60	50	50
	the front	30	60	50	50
5g/second	the back	30	50	40	40
	the front	30	50	40	40
8g/second	the back	20	50	40	40
	the front	20	50	40	40

injection rate	amount of leakage	Comp. Ex. 2	Ex. 5	Ex. 6
3g/second	the back	30	50	60
	the front	30	50	60

Claims

1. An absorbent article which comprises a liquid-impermeable back sheet, a liquid-permeable top sheet, an absorbent provided between the back sheet and the top sheet and a liquid-permeable surface sheet fixed on the top sheet at both ends of the surface sheet at the longitudinal direction of the article, however not fixed thereon at the intermediate part.

2. The article as claimed in Claim 1, in which the surface sheet is shorter than the top sheet at the longitudinal direction of the article when it is not used.

3. The article as claimed in Claim 1, in which the surface sheet has the central part which may fall downwardly of the peripheral part when it has a weight of 40 grams on the central part.

4. The article as claimed in Claim 3, in which the peripheral part of the surface sheet comprises an elastic material.

5. The article as claimed in Claim 3, in which the peripheral part of the surface sheet is provided to be upper than the peripheral part of the article when it is not used.

Fig. 1




Fig. 2

